DTA3514 Datasheet
Product Revision: Rev A

DTA3514
Rev. A
RoHS

BUS A

DIP14

BUS B

www.winford.com

2.30″

0.98″
MTG HOLES
CENTERED

0.30″

0.10″

0.25″

2.00″

0.25″

0.41″
typical

0.062″

○ MOUNTING HOLE, 0.15″ DIA

◎ SOLDER PAD W/ 0.05″ DIA HOLE

DTA3514 Rev A Specifications

| Ambient Temperature	-20°C to 85°C
Ambient Humidity	10% to 90% RH, non-condensing
Voltage	*Contact Winford Engineering
Continuous Current	*Contact Winford Engineering
Screw Terminal Size	Accepts 16 - 26 AWG wire

Contact Winford Engineering with this inquiry. Specifications such as current rating involve component specifications, ambient temperature, max appropriate temperature rise, and the number of simultaneously active conductors. Contact support@winford.com

Part Number Ordering Information

DTA3514   -   [   ]
                1

DIN Clip Mounting Option

1. Mounting Option

- **FT**   Rubber Feet on bottom side of PCB
- **DIN**   DIN Rail Mounting Clips

DTA3514 Stocked Part Numbers

The following part numbers represent standard options and are stocked:

- DTA3514 -FT
- DTA3514 -DIN

For parts other than DTA3514 -*, please see the other datasheets for a list of stocked part numbers.

Notices

1. Drawings and specifications are subject to change without notice.

2. Winford Engineering, LLC does not authorize any of its products for use in military, medical or other life-critical systems and/or devices. Life-critical devices/systems include devices or systems which, a) are intended for surgical implantation into the body, or b) support or sustain life and whose failure to perform can be reasonably expected to result in injury. Winford Engineering, LLC products are not designed with the components required, and are not subject to the testing required to ensure a level of reliability suitable for the treatment and diagnosis of people. Winford Engineering, LLC shall not be held responsible or liable for damages or injury that occur as a result of the use of this product.