

CBHPD50MB-x Cable Datasheet

Product Revision: Rev A
Half-Pitch DSUB 50-pin Male-Male Cables

CBHPD50MB-x Rev A Specifications

Wire	28 AWG, 25 twisted pairs (50 conductors + drain)
Wire shielding	Aluminum foil shield and braid shield with drain wire
Wire jacket color	Beige
Connectors (both)	HPDB50 (50-Pin Half-Pitch DSUB) Male, overmolded shell, with strain relief and latches
Pin mapping	All 1:1
Standard lengths	CBHPD50MB-3 (3ft), CBHPD50MB-6 (6ft)

Twisted Pairs

Note: '{' denotes twisted pairs

{ Pin 1 { Pin 26	{ Pin 13 { Pin 38	{ Pin 25 { Pin 50
{ Pin 2 { Pin 27	{ Pin 14 { Pin 39	- Shield
{ Pin 3 { Pin 28	{ Pin 15 { Pin 40	
{ Pin 4 { Pin 29	{ Pin 16 { Pin 41	
{ Pin 5 { Pin 30	{ Pin 17 { Pin 42	
{ Pin 6 { Pin 31	{ Pin 18 { Pin 43	
{ Pin 7 { Pin 32	{ Pin 19 { Pin 44	
{ Pin 8 { Pin 33	{ Pin 20 { Pin 45	
{ Pin 9 { Pin 34	{ Pin 21 { Pin 46	
{ Pin 10 { Pin 35	{ Pin 22 { Pin 47	
{ Pin 11 { Pin 36	{ Pin 23 { Pin 48	
{ Pin 12 { Pin 37	{ Pin 24 { Pin 49	



Pictured: **CBHPD50MB-6**

Notices

1. Drawings and specifications are subject to change without notice.
2. Winford Engineering, LLC does not authorize any of its products for use in military, medical or other life-critical systems and/or devices. Life-critical devices/systems include devices or systems which, a) are intended for surgical implantation into the body, or b) support or sustain life and whose failure to perform can be reasonably expected to result in injury. Winford Engineering, LLC products are not designed with the components required, and are not subject to the testing required to ensure a level of reliability suitable for the treatment and diagnosis of people. Winford Engineering, LLC shall not be held responsible or liable for damages or injury that occur as a result of the use of this product.